

NAME

aptd – package managing daemon providing a D-Bus interface

SYNOPSIS

aptd [*OPTIONS*]

DESCRIPTION

aptd allows to perform package management tasks, e.g. installing or removing software, using a D-Bus interface. The privileges are handled by PolicyKit so the client application doesn't need to run as root. Furthermore aptd is started by D-Bus activation only when an user calls a method.

OPTIONS

-d, --debug

Show additional information on the command line.

-h, --help

Show information about the usage of the command.

-r, --replace

Replace another aptd instance if it is running.

-p *PROFILE_FILE*

Write profiling data to *PROFILE_FILE* using Python's profiler. This is only of use to developers.

-t, --disable-timeout

Do not shutdown the daemon after an idle time.

--dummy

Instead of applying the changes to the system only show a progress. This option is only usable for developers to locate problems in client applications.

FILES

/etc/apt/apt.conf.d/20dbus

Adds a small post update hook which will emit the org.debian.apt.CacheChanged signal on the system D-Bus to indicate that the cache has been changed and a possible running aptd instance should reload its internal cache.

/usr/share/polkit-1/actions/org.debian.apt.policy

The PolicyKit definitions of the privileges used by aptdaemon, e.g. to install packages. To change the privileges please have a look at **PolicyKit.conf(1)**.

/etc/dbus-1/system.d/org.debian.apt.conf

The D-Bus configuration of the org.debian.apt name space.

DIAGNOSTICS

By default aptdaemon logs to the syslog facility AptDaemon. Furthermore you can use the -d option to get additional information on the command line.

HOMEPAGE

<https://launchpad.net/aptdaemon>

BUGS

You can report bugs at the Launchpad site of aptdaemon: <https://bugs.launchpad.net/aptdaemon/+filebug>

AUTHOR

Sebastian Heinlein <devel at glatzor dot de>

SEE ALSO

aptdcon(1), **org.debian.apt(7)**, **org.debian.apt.transaction(7)**, **PolicyKit.conf(7)**