

**NAME**

chroot – run command or interactive shell with special root directory

**SYNOPSIS**

**chroot** [*OPTION*] *NEWROOT* [*COMMAND* [*ARG*]...]

**chroot** *OPTION*

**DESCRIPTION**

Run *COMMAND* with root directory set to *NEWROOT*.

**--groups=*G\_LIST***

specify supplementary groups as *g1,g2,...,gN*

**--userspec=*USER:GROUP***

specify user and group (ID or name) to use

**--skip-chdir**

do not change working directory to '/'

**--help** display this help and exit

**--version**

output version information and exit

If no command is given, run `"$SHELL" -i` (default: `/bin/sh -i`).

**AUTHOR**

Written by Roland McGrath.

**REPORTING BUGS**

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report chroot translation bugs to <<https://translationproject.org/team/>>

**COPYRIGHT**

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

**SEE ALSO**

chroot(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/chroot>>  
or available locally via: `info '(coreutils) chroot invocation'`