

NAME

docker-system-events - Get real time events from the server

SYNOPSIS

docker system events [OPTIONS]

DESCRIPTION

Get event information from the Docker daemon. Information can include historical information and real-time information.

Docker containers will report the following events:

attach, commit, copy, create, destroy, detach, die, exec_create, exec_detach, exec_start, export, kill, oom, pause, rename

Docker images report the following events:

delete, import, load, pull, push, save, tag, untag

Docker volumes report the following events:

create, mount, unmount, destroy

Docker networks report the following events:

create, connect, disconnect, destroy

OPTIONS

The `--since` and `--until` parameters can be Unix timestamps, date formatted timestamps, or Go duration strings (e.g. 10m, 1h30m) computed relative to the client machine's time. If you do not provide the `--since` option, the command returns only new and/or live events. Supported formats for date formatted time stamps include RFC3339Nano, RFC3339, 2006-01-02T15:04:05, 2006-01-02T15:04:05.999999999, 2006-01-02Z07:00, and 2006-01-02. The local time-zone on the client will be used if you do not provide either a Z or a `+--00:00` timezone offset at the end of the timestamp. When providing Unix timestamps enter seconds[.nanoseconds], where seconds is the number of seconds that have elapsed since January 1, 1970 (midnight UTC/GMT), not counting leap seconds (aka Unix epoch or Unix time), and the optional .nanoseconds field is a fraction of a second no more than nine digits long.

EXAMPLES**Listening for Docker events**

After running `docker events` a container 786d698004576 is started and stopped (The container name has been shortened in the output below):

```
# docker events
2015-01-28T20:21:31.000000000-08:00 59211849bc10: (from whenry/testimage:latest) start
2015-01-28T20:21:31.000000000-08:00 59211849bc10: (from whenry/testimage:latest) die
2015-01-28T20:21:32.000000000-08:00 59211849bc10: (from whenry/testimage:latest) stop
```

Listening for events since a given date

Again the output container IDs have been shortened for the purposes of this document:

```
# docker events --since '2015-01-28'
2015-01-28T20:25:38.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) create
2015-01-28T20:25:38.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) start
2015-01-28T20:25:39.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) create
2015-01-28T20:25:39.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) start
2015-01-28T20:25:40.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) die
2015-01-28T20:25:42.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) stop
2015-01-28T20:25:45.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) start
2015-01-28T20:25:45.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) die
2015-01-28T20:25:46.000000000-08:00 c21f6c22ba27: (from whenry/testimage:latest) stop
```

The following example outputs all events that were generated in the last 3 minutes, relative to the current time on the client machine:

```
# docker events --since '3m'
2015-05-12T11:51:30.999999999Z07:00 4386fb97867d: (from ubuntu-1:14.04) die
2015-05-12T15:52:12.999999999Z07:00 4386fb97867d: (from ubuntu-1:14.04) stop
2015-05-12T15:53:45.999999999Z07:00 7805c1d35632: (from redis:2.8) die
2015-05-12T15:54:03.999999999Z07:00 7805c1d35632: (from redis:2.8) stop
```

If you do not provide the `--since` option, the command returns only new and/or live events.

Format

If a format (`--format`) is specified, the given template will be executed instead of the default format. Go's [text/template](http://golang.org/pkg/text/template/) package describes all the details of the format.

```
# docker events --filter 'type=container' --format 'Type={{.Type}} Status={{.Status}} ID={{.ID}}'
Type=container Status=create ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
Type=container Status=attach ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
Type=container Status=start ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
Type=container Status=resize ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
Type=container Status=die ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
Type=container Status=destroy ID=2ee349dac409e97974ce8d01b70d250b85e0ba8189299c126a87812311951e26
```

If a format is set to `{{ json . }}`, the events are streamed as valid JSON Lines. For information about JSON Lines, please refer to <http://jsonlines.org/>.

```
# docker events --format '{{ json . }}'
{"status":"create","id":"196016a57679bf42424484918746a9474cd905dd993c4d0f4..
```

```
{ "status": "attach", "id": "196016a57679bf42424484918746a9474cd905dd993c4d0f4..
{ "Type": "network", "Action": "connect", "Actor": { "ID": "1b50a5bf755f6021dfa78e..
{ "status": "start", "id": "196016a57679bf42424484918746a9474cd905dd993c4d0f42..
{ "status": "resize", "id": "196016a57679bf42424484918746a9474cd905dd993c4d0f4..
```

Filters

```
$ docker events --filter 'event=stop'
2014-05-10T17:42:14.999999999Z07:00 container stop 4386fb97867d (image=ubuntu-1:14.04)
2014-09-03T17:42:14.999999999Z07:00 container stop 7805c1d35632 (image=redis:2.8)
```

```
$ docker events --filter 'image=ubuntu-1:14.04'
2014-05-10T17:42:14.999999999Z07:00 container start 4386fb97867d (image=ubuntu-1:14.04)
2014-05-10T17:42:14.999999999Z07:00 container die 4386fb97867d (image=ubuntu-1:14.04)
2014-05-10T17:42:14.999999999Z07:00 container stop 4386fb97867d (image=ubuntu-1:14.04)
```

```
$ docker events --filter 'container=7805c1d35632'
2014-05-10T17:42:14.999999999Z07:00 container die 7805c1d35632 (image=redis:2.8)
2014-09-03T15:49:29.999999999Z07:00 container stop 7805c1d35632 (image=redis:2.8)
```

```
$ docker events --filter 'container=7805c1d35632' --filter 'container=4386fb97867d'
2014-09-03T15:49:29.999999999Z07:00 container die 4386fb97867d (image=ubuntu-1:14.04)
2014-05-10T17:42:14.999999999Z07:00 container stop 4386fb97867d (image=ubuntu-1:14.04)
2014-05-10T17:42:14.999999999Z07:00 container die 7805c1d35632 (image=redis:2.8)
2014-09-03T15:49:29.999999999Z07:00 container stop 7805c1d35632 (image=redis:2.8)
```

```
$ docker events --filter 'container=7805c1d35632' --filter 'event=stop'
2014-09-03T15:49:29.999999999Z07:00 container stop 7805c1d35632 (image=redis:2.8)
```

```
$ docker events --filter 'type=volume'
2015-12-23T21:05:28.136212689Z volume create test-event-volume-local (driver=local)
2015-12-23T21:05:28.383462717Z volume mount test-event-volume-local (read/write=true, container=562fe10671e9273da25eed3)
2015-12-23T21:05:28.650314265Z volume unmount test-event-volume-local (container=562fe10671e9273da25eed3)
2015-12-23T21:05:28.716218405Z volume destroy test-event-volume-local (driver=local)
```

```
$ docker events --filter 'type=network'
2015-12-23T21:38:24.705709133Z network create 8b111217944ba0ba844a65b13efcd57dc494932ee2527577758f93
2015-12-23T21:38:25.119625123Z network connect 8b111217944ba0ba844a65b13efcd57dc494932ee2527577758f93
```

```
$ docker events --filter 'type=plugin' (experimental)
2016-07-25T17:30:14.825557616Z plugin pull ec7b87f2ce84330fe076e666f17dfc049d2d7ae0b8190763de94e1f2d10
2016-07-25T17:30:14.888127370Z plugin enable ec7b87f2ce84330fe076e666f17dfc049d2d7ae0b8190763de94e1f2d10
```

OPTIONS

- f, --filter=** Filter output based on conditions provided
- format=""** Format the output using the given Go template
- h, --help[=false]** help for events

--since="" Show all events created since timestamp

--until="" Stream events until this timestamp

SEE ALSO

docker-system(1)