

NAME

fc-query – query font files

SYNOPSIS

fc-query [**-Vh**]

[[**-b**] [**--ignore-blanks**]] [[**-i** *index*] [**--index** *index*]] [[**-f** *format*] [**--format** *format*]] [**--version**] [**--help**] *font-file...*

DESCRIPTION

fc-query queries *font-file*(s) using the normal fontconfig rules and prints out font pattern for each face found. If **--index** is given, only one face of each file is queried, otherwise all faces are queried.

OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

- b** Ignore blanks to compute languages
- i** Only query face indexed *index* of each file.
- f** Format output according to the format specifier *format*.
- V** Show version of the program and exit.
- h** Show summary of options.

font-file

Query *font-file* for font faces.

RETURN CODES

fc-query returns error code 0 for successful parsing, or 1 if any errors occurred or if at least one font face could not be opened.

SEE ALSO

fc-scan(1) **FcFreeTypeQuery**(3) **FcPatternFormat**(3) **fc-cat**(1) **fc-cache**(1) **fc-list**(1) **fc-match**(1) **fc-pattern**(1)

The fontconfig user's guide, in HTML format: </usr/share/doc/fontconfig/fontconfig-user.html>.

AUTHOR

This manual page was updated by Behdad Esfahbod <behdad@behdad.org>.