

NAME

id – print real and effective user and group IDs

SYNOPSIS

id [*OPTION*]... [*USER*]

DESCRIPTION

Print user and group information for the specified *USER*, or (when *USER* omitted) for the current user.

-a ignore, for compatibility with other versions

-Z, --context
print only the security context of the process

-g, --group
print only the effective group ID

-G, --groups
print all group IDs

-n, --name
print a name instead of a number, for **-ugG**

-r, --real
print the real ID instead of the effective ID, with **-ugG**

-u, --user
print only the effective user ID

-z, --zero
delimit entries with NUL characters, not whitespace;
not permitted in default format

--help display this help and exit

--version
output version information and exit

Without any *OPTION*, print some useful set of identified information.

AUTHOR

Written by Arnold Robbins and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report id translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<https://www.gnu.org/software/coreutils/id>>
or available locally via: info '(coreutils) id invocation'