

**NAME**

pfifo\_fast – three-band first in, first out queue

**DESCRIPTION**

pfifo\_fast is the default qdisc of each interface.

Whenever an interface is created, the pfifo\_fast qdisc is automatically used as a queue. If another qdisc is attached, it preempts the default pfifo\_fast, which automatically returns to function when an existing qdisc is detached.

In this sense this qdisc is magic, and unlike other qdiscs.

**ALGORITHM**

The algorithm is very similar to that of the classful **tc-prio**(8) qdisc. **pfifo\_fast** is like three **tc-pfifo**(8) queues side by side, where packets can be enqueued in any of the three bands based on their Type of Service bits or assigned priority.

Not all three bands are dequeued simultaneously - as long as lower bands have traffic, higher bands are never dequeued. This can be used to prioritize interactive traffic or penalize 'lowest cost' traffic.

Each band can be txqueuelen packets long, as configured with **ifconfig**(8) or **ip**(8). Additional packets coming in are not enqueued but are instead dropped.

See **tc-prio**(8) for complete details on how TOS bits are translated into bands.

**PARAMETERS**

txqueuelen

The length of the three bands depends on the interface txqueuelen, as specified with **ifconfig**(8) or **ip**(8).

**BUGS**

Does not maintain statistics and does not show up in tc qdisc ls. This is because it is the automatic default in the absence of a configured qdisc.

**SEE ALSO**

**tc**(8)

**AUTHORS**

Alexey N. Kuznetsov, <kuznet@ms2.inr.ac.ru>

This manpage maintained by bert hubert <ahu@ds9a.nl>