

NAME

viewres - graphical class browser for Xt

SYNOPSIS

viewres [-option ...]

DESCRIPTION

The *viewres* program displays a tree showing the widget class hierarchy of the Athena Widget Set. Each node in the tree can be expanded to show the resources that the corresponding class adds (i.e. does not inherit from its parent) when a widget is created. This application allows the user to visually examine the structure and inherited resources for the Athena Widget Set.

OPTIONS

Viewres accepts all of the standard toolkit command line options as well as the following:

-top name

This option specifies the name of the highest widget in the hierarchy to display. This is typically used to limit the display to a subset of the tree. The default is *Object*.

-variable

This option indicates that the widget variable names (as declared in header files) should be displayed in the nodes rather than the widget class name. This is sometimes useful to distinguish widget classes that share the same name (such as *Text*).

-vertical

This option indicates that the tree should be displayed top to bottom rather left to right.

VIEW MENU

The way in which the tree is displayed may be changed through the entries in the **View** menu:

Show Variable Names

This entry causes the node labels to be set to the variable names used to declare the corresponding widget class. This operation may also be performed with the **SetLabelType(variable)** translation.

Show Class Names

This entry causes the node labels to be set to the class names used when specifying resources. This operation may also be performed with the **SetLabelType(class)** translation.

Layout Horizontal

This entry causes the tree to be laid out from left to right. This operation may also be performed with the *SetOrientation(West)* translation.

Layout Vertical

This entry causes the tree to be laid out from top to bottom. This operation may also be performed with the *SetOrientation(North)* translation.

Show Resource Boxes

This entry expands the selected nodes (see next section) to show the new widget and constraint resources. This operation may also be performed with the *Resources(on)* translation.

Hide Resource Boxes

This entry removes the resource displays from the selected nodes (usually to conserve space). This operation may also be performed with the *Resources(off)* translation.

SELECT MENU

Resources for a single widget class can be displayed by clicking **Button2** on the corresponding node, or by adding the node to the selection list with **Button1** and using the **Show Resource Boxes** entry in the **View** menu. Since **Button1** actually toggles the selection state of a node, clicking on a selected node will cause it to be removed from the selected list.

Collections of nodes may also be selected through the various entries in the **Select** menu:

Unselect All

This entry removes all nodes from the selection list. This operation may also be performed with the *Select(nothing)* translation.

Select All

This entry adds all nodes to the selection list. This operation may also be performed with the *Select(all)* translation.

Invert All

This entry adds unselected nodes to, and removes selected nodes from, the selection list. This operation may also be performed with the *Select(invert)* translation.

Select Parent

This entry selects the immediate parents of all selected nodes. This operation may also be performed with the *Select(parent)* translation.

Select Ancestors

This entry recursively selects all parents of all selected nodes. This operation may also be performed with the *Select(ancestors)* translation.

Select Children

This entry selects the immediate children of all selected nodes. This operation may also be performed with the *Select(children)* translation.

Select Descendants

This entry recursively selects all children of all selected nodes. This operation may also be performed with the *Select(descendants)* translation.

Select Has Resources

This entry selects all nodes that add new resources (regular or constraint) to their corresponding widget classes. This operation may also be performed with the *Select(resources)* translation.

Select Shown Resource Boxes

This entry selects all nodes whose resource boxes are currently expanded (usually so that they can be closed with **Hide Resource Boxes**). This operation may also be performed with the *Select(shown)* translation.

ACTIONS

The following application actions are provided:

Quit()

This action causes *viewres* to exit.

SetLabelType(*type*)

This action sets the node labels to display the widget *variable* or *class* names, according to the argument *type*.

SetOrientation(*direction*)

This action sets the root of the tree to be one of the following areas of the window: *West*, *North*, *East*, or *South*.

Select(*what*)

This action selects the indicated nodes, as described in the **VIEW MENU** section: *nothing* (unselects all nodes), *invert*, *parent*, *ancestors*, *children*, *descendants*, *resources*, *shown*.

Resources(*op*)

This action turns *on*, *off*, or *toggles* the resource boxes for the selected nodes. If invoked from within one of the nodes (through the keyboard or pointer), only that node is used.

WIDGET HIERARCHY

Resources may be specified for the following widgets:

Viewres viewres

```

Paned pane
  Box buttonbox
    Command quit
    MenuButton view
      SimpleMenu viewMenu
        SmeBSB layoutHorizontal
        SmeBSB layoutVertical
        SmeLine line1
        SmeBSB namesVariable
        SmeBSB namesClass
        SmeLine line2
        SmeBSB viewResources
        SmeBSB viewNoResources
    MenuButton select
      SimpleMenu selectMenu
        SmeBSB unselect
        SmeBSB selectAll
        SmeBSB selectInvert
        SmeLine line1
        SmeBSB selectParent
        SmeBSB selectAncestors
        SmeBSB selectChildren
        SmeBSB selectDescendants
        SmeLine line2
        SmeBSB selectHasResources
        SmeBSB selectShownResources
  Form treeform
    Porthole porthole
    Tree tree
      Box variable-name
        Toggle variable-name
        List variable-name
  Panner panner

```

where variable-name is the widget variable name of each node.

SEE ALSO

X(7), xrb(1), listres(1), editres(1), appres(1), appropriate widget documents

COPYRIGHT

Copyright 1994 X Consortium

See X(7) for a full statement of rights and permissions.

AUTHOR

Jim Fulton, MIT X Consortium